



# DAGENITE

**EFB** *Enhanced Flooded Battery*



**DESIGNED FOR  
START-STOP  
VEHICLES**



\*tca

Distributed by

**a-map**  
AL-MUQARRAM AUTO PARTS



[www.dagenitebattery.com](http://www.dagenitebattery.com)

Manufactured by Exide Industries Limited, India

# BRUTE POWER

Instant start, long-lasting  
automotive batteries



**Dagenite** is a brand synonymous with enormous power to start vehicles and keep on feeding modern array of accessories during the drive. With a history of manufacturing automotive batteries stretching over seven decades, Dagenite is a reliable and proven brand name. The all-new version is added with enhanced flooded technology which empowers the range with superior performance over standard flooded batteries.

**Dagenite EFB** batteries remain adequate even at partial state of charge when used to crank modern vehicles. It withstands the rigorous usage for longer lifespan. It adds excellence to driving with faster charging and saves fuel while working in a start-stop system with regenerative braking features. It is available in factory charged fit-n-drive condition. Strong yet ergonomic containers are specially designed to arrest sparks and corrosion. Specially designed plates with superior chemical composition are suitable for working in extreme hot climate.

**MAINTENANCE FREE**

**ENDURES HIGH HEAT**

**QUICK RECHARGE**

**START-STOP READY**

**HOLDS MORE CHARGE**

**POWERS ACCESSORIES**

**SPECIAL PLATES**

**LONGER LIFESPAN**

**FACTORY CHARGED**

## DAGENITE EFB RANGE FOR PASSENGER CAR, UTILITY VEHICLES AND LIGHT COMMERCIAL VEHICLES

| Nomenclature   | Layout |     | Ampere-hour capacity at C20 rating | Cold cranking performance (Amps) SAE/EN1 | Dimensions (mm) |       |        | Charge Indicator |
|----------------|--------|-----|------------------------------------|------------------------------------------|-----------------|-------|--------|------------------|
|                |        |     |                                    |                                          | Length          | Width | Height |                  |
| EFB-M42-B20    | L,0    | R,1 | 40                                 | 340                                      | 197             | 127   | 227    | ✓                |
| EFB-N55-B24-S  | L,0    | R,1 | 50                                 | 430                                      | 238             | 129   | 227    | ✓                |
| EFB-Q85-D23    | L,0    | R,1 | 70                                 | 550                                      | 232             | 172   | 225    | ✓                |
| EFB50-S95-D26  | L,0    | R,1 | 50                                 | 500                                      | 260             | 173   | 225    | ✓                |
| EFB80-S95-D26  | L,0    | R,1 | 80                                 | 680                                      | 260             | 173   | 225    | ✓                |
| EFB90-T110-D31 | L,0    | R,1 | 90                                 | 740                                      | 305             | 173   | 225    | ✓                |
| EFB95-T110-D31 | L,0    | R,1 | 95                                 | 800                                      | 305             | 173   | 225    | ✓                |
| EFB-L1-DIN44   | L,0    | R,1 | 44                                 | 400                                      | 210             | 175   | 190    | ✓                |
| EFB-L1-DIN50   | L,0    | R,1 | 50                                 | 430                                      | 210             | 175   | 190    | ✓                |
| EFB-L2-DIN55   | L,0    | R,1 | 55                                 | 480                                      | 210             | 175   | 190    | ✓                |
| EFB-L2-DIN60   | L,0    | R,1 | 60                                 | 500                                      | 243             | 175   | 190    | ✓                |
| EFB-L3-DIN66   | L,0    | R,1 | 66                                 | 580                                      | 278             | 175   | 190    | ✓                |
| EFB-L3-DIN72   | L,0    | R,1 | 72                                 | 560                                      | 278             | 175   | 190    | ✓                |
| EFB-L3-DIN74   | L,0    | R,1 | 74                                 | 600                                      | 278             | 175   | 190    | ✓                |
| EFB-L4-DIN80   | L,0    | NA  | 80                                 | 750                                      | 313             | 175   | 190    | ✓                |
| EFB-L5-DIN100  | L,0    | NA  | 100                                | 800                                      | 353             | 175   | 190    | ✓                |

## DAGENITE EFB RANGE FOR HEAVY COMMERCIAL VEHICLES

| Nomenclature    | Layout |     | Ampere-hour capacity at C20 rating | Cold cranking performance (Amps) SAE/EN1 | Dimensions (mm) |       |        | Handle      |
|-----------------|--------|-----|------------------------------------|------------------------------------------|-----------------|-------|--------|-------------|
|                 |        |     |                                    |                                          | Length          | Width | Height |             |
| EFB-E41-MF100   | L,0    | R,1 | 100                                | 680                                      | 410             | 176   | 233    | Retractable |
| EFB-F51-MF120   | L,3    | R,4 | 120                                | 780                                      | 505             | 182   | 240    | Rope        |
| EFB-DINB-DIN150 | L,3    | R,4 | 150                                | 850                                      | 513             | 224   | 220    | Rope        |
| EFB-DINB-DIN170 | L,3    | R,4 | 170                                | 900                                      | 513             | 224   | 220    | Rope        |
| EFB-DINB-DIN180 | L,3    | R,4 | 180                                | 950                                      | 513             | 224   | 220    | Rope        |
| EFB-DINC-DIN200 | L,3    | R,4 | 200                                | 1050                                     | 521             | 278   | 242    | Rope        |
| EFB-DINC-DIN225 | L,3    | R,4 | 225                                | 1150                                     | 518             | 275   | 244    | Rope        |



# **DAGENITE** **EFB** Enhanced Flooded Battery



**MAINTENANCE FREE**

**QUICK RECHARGE**

**START-STOP READY**

**HOLDS CHARGE LONGER**



**ENDURES HIGH HEAT**

**POWERS ACCESSORIES**


**LONGER LIFESPAN**

**FACTORY CHARGED**

## KEY TO BATTERY LAYOUT

Left Layout

Right Layout



## TERMINAL DETAILS

| Types of terminals | Tip diameter (f.D)                                     |                                                        |
|--------------------|--------------------------------------------------------|--------------------------------------------------------|
|                    | Positive (mm)                                          | Negative (mm)                                          |
| T1                 | 14.7 $\begin{smallmatrix} 0 \\ -0.3 \end{smallmatrix}$ | 13.0 $\begin{smallmatrix} 0 \\ -0.3 \end{smallmatrix}$ |
| T2                 | 19.5 $\begin{smallmatrix} 0 \\ -0.3 \end{smallmatrix}$ | 17.9 $\begin{smallmatrix} 0 \\ -0.3 \end{smallmatrix}$ |

Nomenclatures conform to JIS 5301-1999 and DIN standards.

All Dagenite EFB batteries are fitted with charge indicator (acid level indicator) and supplied in green container.

**[www.dagenitebattery.com](http://www.dagenitebattery.com)**

Dagenite EFB is a brand owned by  
Exide Industries Limited

59E, Chowringhee Road, Kolkata, WB, India, PIN: 700020

For more details please visit [www.exideindustries.com](http://www.exideindustries.com)

This catalogue is issued to provide outline information only and is not deemed to form part of an offer and contract. Our policy is one of continued improvement and we reserve the right to change details without any prior notice.  
© 2023 Exide Industries Limited, Kolkata, India. All rights reserved.

Unauthorised copying of content of this catalogue is strictly prohibited and may attract punishment under applicable legal provisions

Distributed by



**Al-Muqqaram Auto Parts L.L.C**

P.O. Box: 60235, Dubai, UAE,

Tel: +971 4 2241423, Fax: +971 4 224 1450

[info@a-map.net](mailto:info@a-map.net) [www.a-map.net](http://www.a-map.net)

[/amapglobal](https://www.facebook.com/amapglobal) [/company/a-map](https://www.linkedin.com/company/a-map) [/amap\\_global](https://www.instagram.com/amap_global)

**800 A-MAP (2627)**